

Cross Reference

From AKS 41/41U to AKS 4100/4100U

AKS 41 without bargraph			
Type	Length [mm]	Length [in.]	Code number
AKS 41-3	280	11	084H4053
AKS 41-5	500	19.7	084H4055
AKS 41-8	800	31.5	084H4058
AKS 41-10	1000	39.4	084H4060
AKS 41-12	1200	47.2	084H4062
AKS 41-15	1500	59.1	084H4065
AKS 41-17	1700	66.9	084H4067
AKS 41-22	2200	86.6	084H4072
AKS 41-30	3000	118.1	084H4080

From AKS 41 to AKS 4100 WITH level indication

AKS 41 with bargraph			
Type	Length [mm]	Length [in.]	Code number
AKS 41-3	280	11	084H4153
AKS 41-5	500	19.7	084H4155
AKS 41-8	800	31.5	084H4158
AKS 41-10	1000	39.4	084H4160
AKS 41-12	1200	47.2	084H4162
AKS 41-15	1500	59.1	084H4165
AKS 41-17	1700	66.9	084H4167
AKS 41-22	2200	86.6	084H4172
AKS 41-30	3000	118.1	084H4180

Suitable for R717(ammonia), HCFC, HFC and non corrosive gases/liquids.

Type	AKS 4100 CABLE with HMI		
	Length [mm]	Length [in.]	Code number
AKS 4100	800 to 5000	31.5 to 197	084H4501

Suitable for R717(ammonia), R744 (CO₂) HCFC, HFC and non corrosive gases/liquids.
COAXIAL mandatory for CO₂ applications.

Type	AKS 4100 COAXIAL with HMI		
	Length [mm]	Length [in.]	Code number
AKS 4100	500	19.7	084H4510
AKS 4100	800	31.5	084H4511
AKS 4100	1000	39.4	084H4512
AKS 4100	1200	47.2	084H4513
AKS 4100	1500	59.1	084H4514
AKS 4100	1700	66.9	084H4515
AKS 4100	2200	86.6	084H4516

From AKS 41U to AKS 4100U WITHOUT level indication

AKS 41U without bargraph			
Type	Length [in.]	Length [mm]	Code number
AKS 41U-6"	6	152.4	084H4100
AKS 41U-8"	8	203.2	084H4102
AKS 41U-12"	12	304.8	084H4104
AKS 41U-15.3"	15.3	388.6	084H4106
AKS 41U-19.2"	19.2	487.7	084H4108
AKS 41U-23.1"	23.1	586.7	084H4110
AKS 41U-30"	30	762	084H4112
AKS 41U-35"	35	889	084H4114
AKS 41U-45"	45	1143	084H4116
AKS 41U-55"	55	1397	084H4118
AKS 41U-65"	65	1651	084H4122
AKS 41U-85"	85	2159	084H4126
AKS 41U-105"	105	2667	084H4130
AKS 41U-120"	120	3048	084H4132

Suitable for R717(ammonia), HCFC, HFC and non corrosive gases/liquids.

Type	AKS 4100U CABLE with HMI		
	Length [in.]	Length [mm]	Code number
AKS 4100U	31.5 to 197	800 to 5000	084H4521

Suitable for R717(ammonia), R744 (CO₂) HCFC, HFC and non corrosive gases/liquids.
COAXIAL mandatory for CO₂ applications.

Type	AKS 4100U COAXIAL with HMI		
	Length [in.]	Length [mm]	Code number
AKS 4100U	19.2	487.7	084H4530
AKS 4100U	30	762	084H4531
AKS 4100U	45	1143	084H4532
AKS 4100U	55	1397	084H4533
AKS 4100U	65	1651	084H4534
AKS 4100U	85	2159	084H4535

From AKS 41U to AKS 4100U WITH level indication

AKS 41U with bargraph			
Type	Length [in.]	Length [mm]	Code number
AKS 41U-6"	6	152.4	084H4101
AKS 41U-8"	8	203.2	084H4103
AKS 41U-12"	12	304.8	084H4105
AKS 41U-15.3"	15.3	388.6	084H4107
AKS 41U-19.2"	19.2	487.7	084H4109
AKS 41U-23.1"	23.1	586.7	084H4111
AKS 41U-30"	30	762	084H4113
AKS 41U-35"	35	889	084H4115
AKS 41U-45"	45	1143	084H4117
AKS 41U-55"	55	1397	084H4119
AKS 41U-65"	65	1651	084H4123
AKS 41U-85"	85	2159	084H4127
AKS 41U-105"	105	2667	084H4131
AKS 41U-120"	120	3048	084H4133

* Length not available in the AKS 4100/4100U series
 ** Length only available in a COAXIAL version
 *** Length only available in a CABLE version